



HEATECO (CN 03) WITH A MECHANICAL  
THERMOREGULATOR

CN03 200 MIS F



Net weight	5.48 kg
Maximum power	2000 W
Thermo regulator	mechanical
For room up to	40-60 m <sup>3</sup>
Heating area	16-24 m <sup>2</sup>
Height	0.45 m
Width	0.09 m
Mounting	Freestanding



## Information

HeatEco (CN 03) with a mechanical  
thermoregulator

CN03 200 MIS F

- Maximum power : 2000 W
- Optimal convection
- Adjustable thermoregulator
- Bathroom installation option - splash proof IP24 protection
- Anti-frost protection
- Tip-over protection
- Overheating protection
- Switch with protection cap
- Robust metal construction
- Floor standing

## Serie information

HeatEco (CN 03) with a mechanical  
thermoregulator

CN03 200 MIS F

Robust metal construction of the appliance

Wide range of powers – from 500 W to 3000 W, covering heating area from 4 m<sup>2</sup> to 32 m<sup>2</sup>.

Sensitive  $\pm 1^\circ\text{C}$  capillary thermoregulator 7-40 $^\circ\text{C}$  (values on the dial thermostat: 1 to 6) with accuracy  $\pm 1^\circ\text{C}$